



Ordering

Series 67 Order Key

Prefix	Pres. Cl.	Body Style	Size	Body Matl.	Disc Material	Seat Matl.	Stem Matl.	Special Serv.
67-1	15	L	03	S	N	S	P	LL
67-1	15- 150#	L- Lugged	03- 3"	C- Carbon Steel WCB	S- A351 CF8M Stainless Steel	P- PTFE	P - 17-4 PH SS	BS- Bare Stem
	30- 300#	DF- Double Flanged ISO 5752	04- 4"	S- A351 CF8M STAINLESS STEEL	A- Alloy 20	U- UHMWPE*	A- Alloy 20	LL- Latch Lock 316 SS Handle
	60- 600#	GF- Double Flanged Long Pattern w/ Gate Valve Face to Face ANSI B16.34	06- 6"	CM- A182-F22 Chrome Moly	B- 317 Stainless	K- Peek	B- 317 SS	P-SR- Pneumatic Actuated Spring Return
	90- 900#	BW- Butt Weld End (customer to specify pipe schedule at time of order).	08- 8"	B- 317 Stainless Steel	H- Hastelloy	G- Graphite	H- Hastelloy C	P-DA- Pneumatic Actuated Double Acting
		TP- PDC, Special 3-piece Body	10- 10"	H- Hastelloy	J- Duplex	T- Tungston Coated	J- Duplex	G- 1/4 Turn Worm Gearbox
			12- 12"	K- Super Duplex	K- Super Duplex	HT- NITRIDED A351 CF8M SS	K- Super Duplex	S- Special Engineering Service
			14- 14"	J- Duplex	M- Monel	M- Monel	M- Monel	
			16- 16"	M- Monel	N- NITRIDED A351 CF8M HARDENED SS	I- Inconel	S- 316 SS	
			18- 18"	L- Alloy 600		A- Alloy 20		
			20- 20"			S- A351 CF8M STAINLESS STEEL		
			22- 22"					
			24- 24"					