

**PDC Flanged Series 39  
Butterfly Valve  
4" thru 14" for  
125/150 lb. Flanging**



**Cv Values for PDC Swing Thru Butterfly Valves**

By definition, Cv is the flow coefficient of a control device or flow restriction. Cv is defined as the number of US gallons of 60°F water per minute which will flow through the given restriction with a one pound per square inch pressure drop.

**Cv Values**

(Flow in GPM of 60°F water at 1 psi pressure drop, specific gravity=1)

Valve Size	Disc Angle, Degree								
	10	20	30	40	50	60	70	80	90
4"	13	28	54	98	159	257	391	550	747
5"	21	43	88	158	265	429	636	913	1,272
6"	30	63	126	228	382	632	955	1,370	1,999
8"	53	111	225	406	680	1,125	1,698	2,591	3,853
10"	83	174	351	635	1,063	1,758	2,655	4,052	6,361
12"	120	252	506	915	1,531	2,533	3,826	5,835	9,164
14"	143	302	606	1,096	1,835	3,035	4,584	6,992	10,981

While this information is presented in good faith and believed to be accurate, PDC inc. does not guarantee results from reliance upon such information. Nothing contained herein is to be construed as a warranty or guarantee, expressed or implied, regarding the merchantability, fitness or any other matter with respect to the products. PDC Inc. reserves the right, without notice, to alter or improve the designs of the products herein.